



H.E.R.S. Inc.
 1203 South Parker
 Olathe, Kansas 66061
 Phone: (913) 764-6718

Redmax Blower Specifications/Features

- Tube-mounted speed control allows users to fix the blowing air speed from gentle breeze to hurricane force.
- Blower housing are made from a very high-technology, impact-resistant ABS, rather than the brittle, fiberglass filled, heavy plastics found on many competitors' models.
- Models HBZ2601 and HB280 can also be used with an optional vacuum kits for collecting debris.



Model	Engine Size		Engine Type	Max Horse-power	Air Vol. (*1)	Air Vol. With Tube	Max Air Speed	Dry Weight	Fuel Capacity	Noise Level (*2)	Warranty (*3)		Available in California
	Cu. In.	CC		HP	CFM	CFM	MPH	Lbs.	Fl. Oz.	db(A)	Cons.	Com.	
HB250	1.5	25.4	2-Stroke	1.2	392	363	127	8.4	22.0	73	2 Yrs.	90 Days	n/a
HB280 NEW	1.7	28.0	2-Stroke	1.1	470	425	170	9.4	16.9	70	2 Yrs.	90 Days	HB280-CA
HBZ2601	1.5	25.4	Strato	1.2	378	353	124	8.4	22.0	72	2 Yrs.	2 Yrs.	HBZ2601-CA
EBZ3000RH	1.8	29.5	Strato	1.3	463	374	131	13.4	36.5	69	2 Yrs.	2 Yrs.	EBZ3000-CA
EBZ5100❖	3.1	50.2	Strato	2.3	678	487	171	20.7	70.9	71	2 Yrs.	2 Yrs.	EBZ5100-CA
EBZ5100Q(68dB)	3.1	50.2	Strato	2.1	639	452	159	20.7	70.9	68	2 Yrs.	2 Yrs.	EBZ5100Q-CA
EBZ7100❖	4.0	64.9	Strato	3.9	812	586	205	23.4	70.9	77	2 Yrs.	2 Yrs.	EBZ7100-CA
EBZ8001❖	4.4	71.9	Strato	4.4	915	685	201	25.4	77.7	77	2 Yrs.	2 Yrs.	EBZ8001-CA

(*1) Without cutting head and strap

(*2) ANSI B175.2-2000

(*3) Ignition coil includes lifetime warranty

❖ Available in left-hand hip mount or right-hand tube throttle controls.