



Specifications

3074LP

Engine:

- Generac 990 c.c. LPG vertical shaft V-twin four-cycle air-cooled engine.
- 30 HP output at 3750 RPM.
- 992 cc displacement.
- Electric start.
- Gear driven oil pump.
- Engine-mounted, replaceable 25 micron Generac oil filter.
- Low oil warning horn (98db).
- Dual-Stage Donaldson air cleaner with Turbo pre-cleaner.

Electrical:

- 12 Volt, 450 cold cranking amp, maintenance-free battery.
- 20 amp alternator/stator with regulator-rectifier.
- Seat safety switch shuts off engine when operator leaves the seat.

Fuel Capacity:

- (2) 8 gallon fuel cylinders (DOT certified).

Gauges:

- Tachometer/Hour meter.

Drive system:

- (2) White Hydraulic. 18 c.c. pumps.
- (2) White Hydraulics HB series hydraulic motors; 17.4 c.i. displacement with case flush loop ("Quad Loop").
- (2) 40-micron hydraulic filters.
- (2) Hand-operated forward/reverse steering/braking controls.
- 2.5 gallon hydraulic reservoir.
- (2) External, remote-mounted hydraulic oil coolers.
- Lubrication: Lucas 15w40 Magnum.
- Electric cooling fan mounted above hydraulic pumps.

**Controls:**

- Console mounted electric mower deck height adjustment.
- (2) Hand-operated steering control levers.
- Hand operated PTO switch
- Throttle control and ignition switch.
- Positive lock drum-type parking brake.
- Operator controlled discharge chute "OCDC"

Steering:

- Independent control of drive wheels through steering control levers.

Brakes:

- Dynamic braking through steering levers.
- Parking brake gives positive lockup of drive wheels when applied.

Main Frame:

- All welded six rail tube frame using 1" X 2" X .125" steel tubing. Lifetime warranty.
- Lifetime warranty on suspension front caster assembly and bearings.
- Stainless steel fenders and flip-up floor pan.
- Front casters with independent suspension.
- Suspension seat with Lumbar.
- Engine guard and front bumper.
- Rear hitch with 2000 lb. towing capacity.

Mower Deck:

- (4) Deck leveling bolts.
- Electric Clutch
- Welded baffles.
- Deck height adjusts straight up and down so pitch is always constant.
- Floating deck mounted to rigid frame (does not run on the ground).
- Deck rollers to prevent scalping.
- Keyless sealed spindle.
- 1-1/4" Effective diameter spindle shafts with self-tightening spindle assembly.

**Deck Materials:**

- Ten (10) gauge shell (.135" thickness).
- 1/4" (.250") reinforcing top plate (bolted, not welded).
- Total thickness in critical area =.385".
- One piece cast iron deck spindle housing.
- Vented, split 3/16" steel deep groove pulleys.

Tires/Wheels:

- Rear: 25" X 12" X 9" Turfboss III tubeless ATV-type 4-ply rating (6-8 lbs air pressure).
- Front: 15" X 6.00" X 8" tubeless 4-ply rating

Ground Speed:

- 0-15 mph forward and reverse.

Cutting Height:

- 1" - 5"

Cut Width:

- 74"

Machine Width:

- 79"

Length:

- 84"

Weight:

- 1451 lbs.

Warranty*

- Three-Year Bumper to Bumper, two year parts and labor, 3rd year parts.
 - Lifetime on front fork caster assemblies.
 - Lifetime on front forks against breakage
 - Lifetime on steering levers
 - Three-Year deck spindle
 - Dixie Chopper meets and exceeds all ANSI standards
- *See Authorized Dixie Chopper Dealer for details
* Specifications are subject to change.