



1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718



4RT Reel Trailer



Capacity

- 24,700 lbs. GVWR (Calculated at 15% Tongue Weight)
- 19,700 lbs. Load Capacity

Dimensions

- Overall Length: 29'
- A-Frame: 5'
- Cargo Bed: 24'L x 72"W x 15"H
- Overall Width: 101"
- Reel Size: (4) four each, 72"D x 60"W x 3" Center Hole

Axles

- (3) three 7,000 lbs. Straight Axles
- 12" x 2" Electric Brakes on All Wheels
- (6) six - ST235/80R16LR-E Tires,
- (4) four - 16" x 6" Single Wheels
(8 Holes on 6-1/2" Bolt Circle)
- (1) Pair - Mud Flaps

Reel Racks

- (4) four - Fixed with Heavy Duty Bronze Bearings, Retainer Cap, Pull & Spring Clip
- (4) four - 2-7/8" Reel Bars with Crossarm and
(1) one Locking Collar

Tool Box

- Tool Box Dimensions" 14"H x 13"D x 78" Contoured to A-Frame
- Fabricated 1/8" Smooth Steel Intergrated Construction
- Lift-Up Lid with Security Hasp for Padlock

Tongue, Hitch & Jack

- 5" x 3" Tubular Steel A-Frame
- 6-Position Adjustable Hitch Plate (14" through 27")
- 2-1/2" Lunette Eye, 35,000 lbs. capacity
- 3/8" x 36"L Galvanized Safety Chains with Safety Hooks and Anchor Shackle
- Fixed Binkley, Model 48000 Drop Leg Jack, 12,000 lb. Static Load Capacity

Main Frame

- 5" x 3" Tubular Steel Main Frame
- 5" x 3" Tubular Steel Main Frame at Front of Cargo Bed
- 6" x 3" Tubular Steel Crossmembers at Rear of Cargo Bed

Cargo Bed

- 12 Gauge Smooth Steel Floor
- 3" C-Channel & 3" Angle Crossmembers on 24" Centers
- Sides - 12 Gauge Steel w/3" x 3" Tubular Steel Top Rail & 5" x 3" Lower Rail
- 12"H x 2"W Vertical Guide Slots for Drop-In 2"W Lumber for Removable Tailgate
- Rear Drop Leg Stabilizing Jacks

Fenders

- Fabricated 1/8" Steel Diamond Tread Plate Fender
- Integrated Construction with Cat Walks

Catwalk

- 1/8" Steel Diamond Tread, Mounted on 4" x 2" Tubular Perimeter Frame
- Full Length of Cargo Bed, Fore and Aft of Fenders

4RT Trailer Spec.'s Con't.

Paint

- Trailer is Completely Sandblasted
- Seams are Sealed with Paintable Caulk
- Rust Prohibitive Two-Part Epoxy Polyamide Primer
- Two-Part Acrylic Polyurethane Topcoats (Standard Colors Safety Yellow and White)
- All Attachments Painted before Assembly and Installed with Serviceable Fasteners

12 Volt Wiring System

- ICC & DOT Approved Lights
- Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights
- S.O. Cable Wiring Loom, Clamped on 16" Centers with Rubber Lined Clamps
- Wiring Loom Terminated in Junction Boxes
- Connections Soldered and Sealed with Heat Shrink Tubing
- 32" Pigtail w/6-Way Aluminum Die Cast Plug, Terminated at Junction Box
- Breakaway Kit with Sealed Lead Acid Battery and Trickle Charger

OPTIONS

Reel Racks

- 96" Reel Diameter in Lieu of 72"
- 12" Tension Brake Package
- 16" Tension Brake Package
- Hydraulic Rewind

Optional Spare Tire & Wheels

- Wheel Chock Holders, with Rubber Wheel Chocks, 7"H x 10"L x 8"W

Hitch & Jack Options

- 3" Lunette Eye (In Lieu of 2-1/2" Eye)
- Visible Registration Holder

Cargo Bed Options

- Safety Cone Holder
- Additional D-Rings

Wiring & Light Bar Options

- Warner 6-Way Connector in Lieu of Standard 6-Way Connector
- Solar Charged Breakaway Kit In Lieu of Standard Kit
- LED Lights