



1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718

CSLT-202 Utility / Skid Loader Trailer



Capacity

- 10,000 lbs. Load Capacity
- Approx. 4,000 lbs. Curb Weight
- 14,000 lbs. GVWR (Calculated at 15% Tongue Weight)

Dimensions

- 16' Tilt Deck Length, 48" Fixed Flat Bed Area,
with 16" Entrance Ramp
- 60" Tongue Length
- 102" Overall Width
- 81" Deck Width between Fenders
- 24" Deck Height

Axles

- 6,000# Single Dexter Torflex Axle
- 12" x 2" Electric Brakes
- 8 Bolt Hubs
- (4) four - ST235/80R16LR-E Tires
- (4) four - 16" x 6" White Mod Wheels
(8 Hole on 6-1/2" Bolt Circle)
- Fenders Fabricated from 1/8" Steel Tread Plate

Equipment Loading

- Tilt Deck with Low Loading Angle
- Spring Loaded Tilt Deck Latching System
- 12" Tapered Entrance Ramp

A-Frame Tongue & Hitch

- 2-5/16" Ball Coupler or 2-1/2" Lunette Eye (Your Choice)
- 10,000 lbs. Drop Leg Jack
- 3/8" Galvanized Safety Chains with
Safety Latch Hooks and Anchor Shackle
- 1-3/16" Cold Rolled Tilt Hinge Pins

Main Frame

- 6" Channel Main Frame
- 3" Channel Crossmembers
- Stake Pockets (4 Per Side)

Floor

- 2" Oak Deck - Installed with 1/4" Floor Screws at
Every other Cross Member
- Each Board Anchored both Ends with 5/16" Carriage Bolts

12 Volt Wiring System

- ICC & DOT Approved Lights
- Sealed Beam Rubber Mounted Stop, Turn, Tail
and Marker Lights
- S.O. Cable Wiring Loom, Clamped on 16"
Centers with Rubber Lined Clamps
- Wiring Loom Terminated in Junction Boxes
- Connections Soldered and Sealed with Heat Shrink Tubing
- 32" Pigtail w/6-Way Aluminum Die Cast Plug, or 7-Way Plug,
Terminated at Junction Box
- Breakaway Kit with Sealed Lead Acid Battery and Trickle Charger

Paint

- Trailer is Completely Sandblasted
- Seams are Sealed with Paintable Caulk
- Rust Prohibitive Two-Part Epoxy Polyamide Primer
- Two-Part Acrylic Polyurethane Topcoats
(Standard Colors Black and White)
- All Attachments Painted before Assembly and Installed
with Serviceable Fasteners
- 2" Red/White Reflective Tape on Both Sides of Trailer



OPTIONS

Axle Options

- Surge Brakes w/adj. 3" Eye w/adj. 2-5/16" Ball Coupler
- Electrastar Brake Actuator (Trailer Mounted)
- Replacement Electrastar In-Cab Controller

Optional Spare Tire/Wheel

- Spare Tire / Wheel (7K Axle) - ST235/80R16LR-E Tires
- Spare Tire / Wheel Wheel Holder (for trailer or skid loader)

Optional Jacks, Couplers and Tool Box

- 3" Lunette Eye in Lieu of 2-1/2"
- Replacement or Additional 2-1/2" Lunette
- Replacement or Additional 2-5/16" Ball Coupler

Misc. Optional

- Rub Rail
- LED Lights (in Lieu of Standard)
- Visible Registration Holder
- 5/8" D-Rings, 19,000 lb.. Capacity (Each)
- Backup Lights, Sealed Beam Rubber Mounted

