



Specifications

Classic 2550

Engine:

- Kohler CV730 vertical shaft V-twin Four-cycle air cooled engine.
- 25 HP output at 3750 RPM.
- 725 cc displacement.
- Electric start.
- Gear driven oil pump.
- Engine mounted replaceable 25 micron Kohler oil filter.
- Low oil warning horn (98db).
- Pulse fuel pump.
- Kohler supplied exhaust.

Electrical:

- 12 Volt, 300 cold cranking amps, maintenance free battery.
- 20 amp alternator/stator with regulator-rectifier.
- Electric start.
- Seat safety switch shuts off engine when operator leaves the seat.

Fuel Capacity:

- 6.0 US Gallons.

Gauges:

- Tachometer/Hour meter

Drive system:

- Two (2) White 13cc Hydraulic Pumps.
- Two (2) White Hydraulics HB series hydraulic motors; 15.1 c.i. displacement with case flush loop ("Quad Loop").
- Two (2) 40-micron hydraulic filters.
- Two (2) Hand operated forward/reverse steering/braking controls.
- 2.5 gallon hydraulic reservoir.
- Two (2) External remote mounted hydraulic oil coolers.
- Lubrication: Lucas 15w40 Magnum.

**Controls:**

- Foot operated mower deck height adjustment.
- Two (2) Hand operated steering control levers.
- Hand operated PTO switch
- Throttle control.
- Ignition switch.
- Choke.
- Dual band type parking brake.
- Operator Controlled Discharge Chute "OCDC"

Steering:

- Independent control of drive wheels through steering control levers.

Brakes:

- Dynamic braking through steering levers.
- Parking brake gives positive lockup of drive wheels when applied.

Main Frame:

- All welded six rail tube frame using 1" X 2" X .125" steel tubing. **Life-time warranty.**
- Stainless steel Flip up floor pan for easy access to deck.
- Stainless steel fenders.
- Seat with armrests.
- Engine guard and front bumper.
- Rear hitch with 2000 lb. towing capacity.
- Life-time warranty on front caster and caster bearings.

Mower Deck:

- Electric Clutch
- Four (4) Deck leveling bolts.
- Welded baffles.
- Deck height adjusts straight up and down so pitch is always constant.
- Floating deck mounted to rigid frame (does not run on the ground).
- Deck rollers to prevent scalping.
- Keyless sealed spindle.
- 1-1/4" Effective diameter spindle shafts with self-tightening spindle assembly.

**Deck Materials:**

- Ten (10) gauge shell (.135" thickness).
- 3/16" (.187") reinforcing top plate.
- Total thickness in critical area = .322".
- One piece cast iron deck spindle housing.
- Vented, split 3/16" steel deep groove pulleys.

Tires/Wheels:

- Rear: 24" X 11" X 10" Turf Boss IV tubeless ATV type 4-ply rating
- Front: 13" X 6.50" X 6" tubeless 4-ply rating

Ground Speed:

- 0-11.5 mph forward and reverse.

Cutting Height:

- 1" to 5"

Cut Width:

- 50"

Machine Width:

- 54"

Length:

- 76"

Weight:

- 1003 lbs.

Warranty*

- Three-Year Bumper to Bumper, two year parts and labor, 3rd year parts.
- Kohler engine has 2 Year Warranty.
- Lifetime on front fork caster assemblies.
- Lifetime on front forks against breakage
- Lifetime on steering levers
- Three-Year deck spindle
- Dixie Chopper meets and exceeds all ANSI standards

- * See Authorized Dixie Chopper Dealer for details
- Specifications are subject to change