



Specifications

Classic 2760

Engine:

- Generac 27 Hp vertical shaft V-twin Four-cycle air-cooled engine.
- 27 Hp output at 3750 RPM.
- 760 c. c. displacement.
- Electric start.
- Gear-driven oil pump.
- Engine-mounted, replaceable, 25 micron Generac oil filter.
- Low oil warning horn (98db).
- Pulse fuel pump.
- Dual-stage Donaldson air cleaner with Turbo pre-cleaner.

Electrical:

- 12 Volt, 300 cold cranking amps, maintenance-free battery.
- 20 amp alternator/stator with regulator-rectifier.
- Seat safety switch shuts off engine when operator leaves the seat.

Fuel Capacity:

- 6.0 US Gallons.

Gauges:

- Tachometer/Hour meter.

Drive system:

- (2) White Hydraulic 13 c.c. pumps.
- (2) White Hydraulics HB series hydraulic motors; 15.1 cu. in. displacement with case flush loop ("Quad Loop").
- (2) 40-micron hydraulic filters.
- (2) Hand-operated forward/reverse steering/braking controls.
- 2.5 gallon hydraulic reservoir tank.

**Drive system:**

- External, remote mounted hydraulic oil cooler.
- Lubrication: Lucas 15w40 Magnum.

Controls:

- Console mounted electric mower deck height adjustment.
- (2) Hand-operated steering control levers.
- Hand operated PTO switch
- Throttle, choke, and ignition switch.
- Dual band-type parking brake.
- Operator controlled discharge chute "OCD" "

Steering:

- Independent control of drive wheels through steering control levers.

Brakes:

- Dynamic braking through steering levers.
- Parking brake gives positive lockup of drive wheels when applied.

Main Frame:

- All welded six rail tube frame using 1" X 2" X .125" steel tubing. Lifetime warranty.
- Lifetime warranty on front caster assembly and bearings.
- Stainless steel fenders.
- Stainless steel flip-up floor pan.
- Seat with armrest.
- Engine guard and front bumper.
- Rear hitch with 2000 lb. towing capacity.

Mower Deck:

- Electric clutch.
- (4) Deck leveling bolts.
- Welded baffles.
- Deck height adjusts straight up and down so pitch is always constant.

**Mower Deck:**

- Floating deck mounted to rigid frame (does not run on the ground).
- Deck rollers to prevent scalping.
- Keyless spindle.
- 1-1/4" Effective diameter spindle shafts with self-tightening spindle assembly.

Deck Materials:

- Ten (10) gauge shell (.135" thickness).
- 3/16" (.187") reinforcing top plate (bolted, not welded).
- Total thickness in critical area = .322".
- One piece cast iron deck spindle housing.
- Vented, split 3/16" steel deep groove pulleys.

Tires/Wheels:

- Rear: 24" X 11" X 10" Turf Boss IV tubeless ATV type 4-ply rating (6-8 lbs air pressure).
- Front: 13" X 6.50" X 6" tubeless 4-ply rating.

Ground Speed:

- 0-11.5 mph forward and reverse.

Cutting Height:

- 1" - 5"

Cut Width:

- 60"

Machine Width:

- 64.5"

Length:

- 76"

Weight:

- 1125 lbs.



Warranty*

- Three-Year Bumper to Bumper, two year parts and labor, 3rd year parts.
 - Lifetime on front fork caster assemblies.
 - Lifetime on front forks against breakage
 - Lifetime on steering levers
 - Three-Year deck spindle
 - Dixie Chopper meets and exceeds all ANSI standards
- * See Authorized Dixie Chopper Dealer for details
- Specifications are subject to change.