



1203 South Parker  
Olathe, Kansas 66061  
Phone: 913.764.6718

## OW10-12K Over the Wheel Flat Bed Trailer



### Capacity

- 23,500 lbs. GVWR (Calculated at 15% Tongue Weight)
- 18,500 lbs. Load Capacity
- Approx. 5,000 lbs. Curb Weight

### Dimensions

- 20" Flat Deck Length
- 60" Tongue Length
- 5' Beavertail
- Overall Width: 100"
- 33-1/2" Deck Height

### Axles

- 10,000 lbs. GD Tandem Dexter Axles
- 12-1/4" x 3-3/8" Electric Brakes on All Wheels
- 8 Bolt Hubs
- (8) eight - LT235/80R16LR-E Tires,
- (8) eight - 16" x 6" Dual Wheels
- (1) one Pair of Mud Flaps
- Slipper Spring Suspension

### Loading Ramps

- 60"L x 18"W Self-Supporting / Adjustable / Fold Up Ramps with Spring Assist
- 10 Degree Beavertail Angle

### Tongue, Hitch & Jack

- 12" x 16# Wide Flange Beam
- 6-Position Adjustable Hitch Plate (14" through 27")
- 2-1/2" Lunette Eye,
- 3/8" Galvanized Safety Chains with Safety Latch Hooks and Anchor Shackle
- Single, 12,000 lb. Binkley Model 48000 Drop Leg Jack w/handle

### Main Frame

- 12" x 16# Wide Flange Beam
- 3" Channel Crossmembers on Approx. 18" Centers
- 6" Channel Side Rails
- 6" Channel Headboard (3-1/2" Above Deck)
- Stake Pockets (7 per side)

### Paint

- Trailer is Completely Sandblasted
- Seams are Sealed with Paintable Caulk
- Rust Prohibitive Two Part Epoxy Polyamide Primer
- Two Part Acrylic Polyurethane Topcoats (Standard Colors Black and White)
- All Attachments Painted before Assembly and Installed with Serviceable Fasteners
- 2" Red/White Reflective Tape on both sides of Trailer



### Flooring

- 2" Oak Deck - Installed with 1/4" Floor Screws
- Each Board Anchored both ends with 5/16" Carriage Bolts

### 12 Volt Wiring System

- ICC & DOT Approved Lights
- Sealed Beam Rubber Mounted Stop, Turn, Tail and Marker Lights
- S.O. Cable Wiring Loom, Clamped on 16" Centers with Rubber Lined Clamps
- Wiring Loom Terminated in Junction Boxes
- Connections Soldered and Sealed with Heat Shrink Tubing
- 32" Pigtail w/6-way Aluminum Die Cast Plug, Terminated at Junction Box
- Breakaway Kit, with Sealed Lead Acid Battery & Trickle Charger

### Options

- Deck Length Variations
- Axles: 10,000 lbs. and 12,000 lbs. with Electric Brakes
- Axles: 10,000 lbs. and 12,000 lbs. with Air Brakes
- Electrastar Brake Actuator In-Cab Controller
- Spare Tire
- Jacks, Couplers and Tool Box
- Tool Box, Chain Tray, Binder Rack
- Goosenecks
- Rub Rail
- Expanded Metal A-Frame Bottom
- And More...