



1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718

PT122XL Pole Trailer



Capacity

- 13,500 lbs. GVWR (Calculated at 15% Tongue Weight)
- 10,200 lbs. Load Capacity

Dimensions

- Length Adjustments: 24' / 31' / 38'
- Cargo Bed: 12'L x 64"W x 15"H
- Overall Width: 86"
- Bolster Height: 42" (45" with Optional removable bolsters)

Axles

- 6,000 lbs. Tandem Dexter Straight Axles - (Optional 7K & 8K)
- 12" x 2" Electric Brakes on All Wheels
- Torflex Suspension
- (4) four - ST235/80R16LR-E Tires,
3,042 lbs. each, Single Wheel Application
- (4) four - 16" x 6" Single Wheels
(8 Holes on 6-1/2" Bolt Circle)
- (1) Pair - Mud Flaps
- (1) Pair - Fender Mounted Wheel Chock Holders
(Wheel Chocks Not Included)

Pole Bolsters

- Front Bolster: 45" wide Fixed
(Mounted on Extendable Tongue)
- Center Bolster: 64" wide w/Pole Stops
(Built into Front Wall of Cargo Bed)
- Rear Bolster: 64" wide w/Pole Stops
(Built into Tailgate - 2" x 2"
Tubular Construction)
- (4) four - Heavy Duty Ratchet Type Winch Binders with Breaker Bar
- (4) four - 15' Long x 4" wide x 12,000 lbs. Nylon Straps

Pockets for Removable Reel Racks

- (1) pair - 3" Receiver Tubes, Mounted inside Cargo Bed Sidewalls

Tongue & Hitch

- 6" x 4" x 1/4" Wall Extendable Tongue
w/Lubricated Steel Wear Pads
- 6-Position Adjustable Hitch Plate
- 2-1/2" Lunette Eye 35,000 lbs. Capacity
- 3/8" 36"L Galvanized Safety Chains with
Safety Latch Hooks and Anchor Shackles

A-Frame & Jack

- 6" x 2" Tubular Steel A-Frame
- Fixed Binkley, Model 48000 Drop Leg Jack,
12,000 lb. Static Load Capacity

Main Frame

- 6" x 3" Tubular Steel Main Frame
- 10" x 6" Receiver Tube
- 7" x 3" Tubular Steel Crossmembers Under Center
and Rear Bolsters
- 3" Structural C-Channel Crossmembers on
14-1/2" Centers Under Cargo Bed Floor

Cargo Bed

- Interior Dimensions: 142"L x 64"W x 15"H with Reinforced
Fold Down Tailgate
- Floor: 1/8" Smooth Steel Construction
- Sidewalls: 12 Gauge Formed in Brake for Added Strength
- Tailgate: Tubular Construction, w/ Offset Hinges so Debris
is Easily Cleared
- (4) four - 5/8" D-Rings, 19,000 lbs. Capacity each,
Floor Mounted (1) one each Corner

Fenders & Catwalk

- Fabricated 1/8" Steel Diamond Tread Plate Fender Construction
- (4) four - Roll-Off Fender Guards, Prevents Damage to Fenders
when "Wrecking"

PT122XL Trailer Spec.'s Con't.

Tool Box

- Tool Boxes Dimensions: 14"H x 24"D x 64"W
- Fabricated from 1/8" Smooth Steel Integrated Construction
- (2) Side Entry Doors with Twist Latches and Key Locks
- Weather Tight Rubber Gaskets

Paint

- Trailer is Completely Sandblasted
- Seams are Sealed with Paintable Caulk
- Rust Prohibitive Two-Part Epoxy Polyamide Primer
- Two-Part Acrylic Polyurethane Topcoats
(Standard Colors Safety Yellow and White)
- All Attachments Painted before Assembly and Installed
with Serviceable Fasteners

12 Volt Wiring System

- ICC & DOT Approved Lights
- Sealed Beam Rubber Mounted Stop, Turn, Tail
and Marker Lights
- S.O. Cable Wiring Loom, Clamped on 16"
Centers with Rubber Lined Clamps
- Wiring Loom Terminated in Junction Boxes
- Connections Soldered and Sealed with Heat Shrink Tubing
- Internal Wiring in Tongue Extension, Receptacle at Each Pin Location
- 36" Pigtail w/6-Way Aluminum Die Cast Plug, or 7-Way Plug,
Terminated at Junction Box
- 6-Way Aluminum Die Cast Plug (Truck Side) in Rear Butt Tube
for Light Bar Hook-Up
- Breakaway Kit with Sealed Lead Acid Battery and
Trickle Charger

OPTIONS

Axle Options

- 7,000 lb. Tandem - Payload: 12,000 lbs. GVWR 15,000 lbs.
12" x 2" Electric Brakes
(4) four - ST235/80R16LR-E, (14 Ply) Capacity 3,520 lbs.
- 8,000 lbs. Tandem - Payload: 13,500 lbs. GVWR 16,500 lbs.
12-1/4" x 3-3/8" Electric Brakes
(4) four - 215/75R/17.5 LR-H, Capacity 4,805 lbs.

Optional Spare Tire & Wheel

- ST235/80R16 LR-E (6K & 7K Axle)
- 215/75R/17.5 LR-H (8K Axle)
- Rubber Wheel Chocks, 7"H x 10"L x 8"W

Front Bolster Options (Mounted on Extendable Tongue)

- 64"W Tubular Bolster, Pole Stops, Winch Binder
and Nylon Strap (In Lieu of 45" Front Bolster)
- U-Type Single Pole Cradle
- Winch Binder and Nylon Strap (In Lieu of 45" Front Bolster)
- (4) - 30'L Nylon Winch Strap in Lieu of 15'
- 60"W (45" ID) 3" Double C-Channel Bolster
Winch Binder and Nylon Strap (In Lieu of 45" Front Bolster):
with 9" Chain Adjusted Stanchions
with 21" Lever Lock Stanchions

Removable Reel Rack Options

- (1) pair - 36"H Reel Stands w/3" Receiver Tubes
(Reel Bar Not Included)
- Additional (1) pair - 3" Receiver Tubes Only
- 2-7/8" Reel Bar w/(2) Locking Collars
- Standard Reel Rack Package:
 - (1) pair - 36"H Reel Stands
 - (1) pair - 3" Receiver Tubes
 - (1) 2-7/8" Reel Bar w/(2) Locking Collars
 - Maximum Reel Size - 68"D x 50"W x 2,200 lbs. Capacity
- Reel Rack w/HD Bronze Bushing Package:
 - (1) pair - 36"H Reel Stands with Bronze Bushing
 - (1) pair - 3" Receiver Tubes
 - (1) 2-7/8" Reel Bar w/(1) Crossarm and (1) Locking Collar
 - Maximum Reel Size - 68"D x 50"W x 3,500 lbs. Capacity

Optional Removable Bolsters (Center & Rear)

- 89" Wide Removable 3" Double C-Channel Bolsters
Includes Your Choice of Stanchions:
with 9" Chain Adjusted Stanchions
with 21" Lever Lock Adjusted Stanchions

Optional Reel Racks with Overspin/Tensioning Brakes

- 8" Overspin Brake Package:
 - 8" Brake w/8" x 7/16" Solid Stainless Disc,
Cast Aluminum Caliper and Tension Adjusting Handle
 - (1) pair - 36"H Reel Stands with Bronze Bushings
 - (1) 2-7/8" Reel Bar with (1) Crossarm and (1) Locking
Collar
 - Maximum Reel Size 68"D x 48"W x 2,500 lbs.
- 12" Medium Duty Tensioning Brake Package:
 - 12" Tension Brake with 12" x 5/8" Solid Bronze Disc.
Cast Steel Caliper and Tension Adjusting Handle
 - (1) pair - 36"H Reel Stands with Heavy Duty Bronze Bearings
 - (1) 2-7/8" Reel Bar with (1) Crossarm and
(1) Locking Collar
 - Maximum Reel Size 68"D x 48"W x 3,000 lbs.

Hitch & Jack Options

- 3" Lunette Eye (In Lieu of 2-1/2" Eye)
- Visible Registration Holder
- Full Width Jack Handle Extension
 - Add to One Side
 - Add to Both Sides (Requires Store-Away Handle)

Cargo Bed Options

- (4) - 9" Wide x 9" Deep Open Top Storage Bins
Located Front and Rear of Fenders to
Roll-Off Fender Guards
- Additional D-Rings
- Chains on Tailgate

Wiring & Light Bar Options

- Light Bar
 - (2) Rubber Mounted Sealed Beam Lights (Stop Turn and Tail)
 - 36"L x 4" x 4" Tubular Steel Body
 - Chain Adjusted Mounting Base
 - 25' of Cable with 6-Way Aluminum Die Cast Connector
- Warner 6-Way Connector in Lieu of Standard 6-Way Connector
- Solar Charged Breakaway Kit In Lieu of Standard Kit