



1203 South Parker  
Olathe, Kansas 66061  
Phone: 913.764.6718

## PT92XL Pole Trailer



### Capacity

- 13,000 lbs. GVWR (Calculated at 15% Tongue Weight)
- 10,200 lbs. Load Capacity

### Dimensions

- Length Adjustments: 20' / 25' / 30'
- Cargo Bed: 9'L x 64"W x 15"H
- Overall Width: 86"
- Bolster Height: 42" (45" with Optional removable bolsters)

### Axles

- 6,000 lbs. Tandem Dexter Straight Axles - (Optional 7K & 8K)
- 12" x 2" Electric Brakes on All Wheels
- 3,500 lbs. 5 Leaf Slipper Springs
- Reinforced Spring Hangers with  
3" Structural C-Channel Crossmembers
- (4) four - ST235/80R16LR-E Tires,  
3,042 lbs. each, Single Wheel Application
- (4) four - 16" x 6" Single Wheels  
(8 Holes on 6-1/2" Bolt Circle)
- (1) Pair - Mud Flaps
- (1) Pair - Fender Mounted Wheel Chock Holders  
(Wheel Chocks Not Included)

### Pole Bolsters

- Front Bolster: 45" wide removable  
(Mounted on Extendable Tongue)
- Center Bolster: 64" wide w/Pole Stops  
(Built into Front Wall of Cargo Bed)
- Rear Bolster: 64" wide w/Pole Stops  
(Built into Tailgate - 2" x 2"  
Tubular Construction)
- (4) four - Heavy Duty Ratchet Type Winch Binders with Breaker Bar
- (4) four - 15' Long x 4" wide x 12,000 lbs. Nylon Straps

### Pockets for Removable Reel Racks

- (1) pair - 3" Receiver Tubes, Mounted inside Cargo Bed Sidewalls

### Tongue & Hitch

- 6" x 4" x 1/4" Wall Extendable Tongue  
w/Lubricated Steel Wear Pads
- 6-Position Adjustable Hitch Plate
- 2-1/2" Lunette Eye, 35,000 lbs. Capacity
- 3/8" x 36"L Galvanized Safety Chains with  
Safety Latch Hooks and Anchor Shackle

### A-Frame & Jack

- 6" x 2" Tubular Steel A-Frame
- Fixed Binkley, Model 48000 Drop Leg Jack,  
12,000 lb. Static Load Capacity

### Main Frame

- 6" x 3" Tubular Steel Main Frame
- 8" x 6" Receiver Tube
- 6" x 4" Tubular Steel Crossmembers Under Center  
and Rear Bolsters Channel Crossmembers
- 3" Structural C-Channel Crossmembers on  
14-1/2" Centers Under Cargo Bed Floor

### Cargo Bed

- Interior Dimensions: 9'L x 64"W x 15"H with Reinforced  
Fold Down Tailgate
- Floor: 1/8" Smooth Steel Construction
- Sidewalls: 12 Gauge Formed in Brake for Added Strength
- Tailgate: Tubular Construction, w/ Offset Hinges so Debris  
is Easily Cleared
- (4) four - 5/8" D-Rings, 19,000 lbs. Capacity each,  
Floor Mounted (1) one each Corner

### Fenders & Catwalk

- Fabricated 1/8" Steel Diamond Tread Plate Fender Construction
- (4) four - Roll-Off Fender Guards, Prevents Damage to Fenders  
when "Wrecking"

## PT92XL Trailer Spec.'s Con't.

### Tool Box

- Tool Boxes Dimensions: 14"W x 24"D x 64"W
- Fabricated from 1/8" Smooth Steel Intergrated Construction
- (2) Side Entry Doors Key Locked with Twist Latches
- Weather Tight Rubber Gaskets

### Paint

- Trailer is Completely Sandblasted
- Seams are Sealed with Paintable Caulk
- Rust Prohibitive Two-Part Epoxy Polyamide Primer
- Two-Part Acrylic Polyurethane Topcoats  
(Standard Colors Safety Yellow and White)
- All Attachments Painted before Assembly and Installed  
with Serviceable Fasteners

### 12 Volt Wiring System

- ICC & DOT Approved Lights
- Sealed Beam Rubber Mounted Stop, Turn, Tail  
and Marker Lights
- S.O. Cable Wiring Loom, Clamped on 16"  
Centers with Rubber Lined Clamps
- Wiring Loom Terminated in Junction Boxes
- Connections Soldered and Sealed with Heat Shrink Tubing
- Internal Wiring in Tongue Extension, Receptacle at each  
Pin Location
- 36" Pigtail w/6-Way Aluminum Die Cast Plug, or 7-Way Plug,  
Terminated at Junction Box
- 6-Way Aluminum Die Cast Plug (Truck Side) in Rear Butt  
Tube for Light Bar Hook-up
- Breakaway Kit with Sealed Lead Acid Battery and  
Trickle Charger

---

## OPTIONS

### Axle

- 7,000 lb. Tandem - Payload: 12,000 lbs. GVWR 15,000 lbs.  
12" x 2" Electric Brakes  
(4) four - ST235/80R16LR-E, (14 Ply) Capacity 3,520 lbs.
- 8,000 lbs. Tandem - Payload: 13,500 lbs. GVWR 16,500 lbs.  
12-1/4" x 3-3/8" Electric Brakes  
(4) four - 215/75R/17.5 LR-H, Capacity 4,805 lbs.

### Spare Tire & Wheel

- ST235/80R16 LR-E (6K & 7K Axle)
- 215/75R/17.5 LR-H (8K Axle)
- Rubber Wheel Chocks, 7"H x 10"L x 8"W

### Front Bolster (Mounted on Extendable Tongue)

- 64"W Tubular Bolster, Pole Stops, Winch Binder  
and Nylon Strap (In Lieu of 45" Front Bolster)
- U-Type Single Pole Cradle
- Winch Binder and Nylon Strap (In Lieu of 45" Front Bolster)
- (4) - 30'L Nylon Winch Strap in Lieu of 15'
- 60"W (45" ID) 3" Double C-Channel Bolster  
Winch Binder and Nylon Strap (In Lieu of 45" Front Bolster):  
with 9" Chain Adjusted Stanchions  
with 21" Lever Lock Stanchions

### Removable Reel Rack

- (1) pair - 36"H Reel Stands w/3" Receiver Tubes  
(Reel Bar Not Included)
- Additional (1) pair - 3" Receiver Tubes Only
- 2-7/8" Reel Bar w/(2) Locking Collars
- Standard Reel Rack Package:
  - (1) pair - 36"H Reel Stands
  - (1) pair - 3" Receiver Tubes
  - (1) 2-7/8" Reel Bar w/(2) Locking CollarsMaximum Reel Size - 68"D x 50"W x 2,200 lbs. Capacity
- Reel Rack w/HD Bronze Bushing Package:
  - (1) pair - 36"H Reel Stands with Bronze Bushing
  - (1) pair - 3" Receiver Tubes
  - (1) 2-7/8" Reel Bar w/(1) Crossarm and (1) Locking CollarMaximum Reel Size - 68"D x 50"W x 3,500 lbs. Capacity

### Reel Racks with Overspin/Tensioning Brakes

- 8" Overspin Brake Package:
  - 8" Brake w/8" x 7/16" Solid Stainless Disc,  
Cast Aluminum Caliper and Tension Adjusting Handle
  - (1) pair - 36"H Reel Stands with Bronze Bushings
  - (1) 2-7/8" Reel Bar with (1) Crossarm and (1) Locking  
CollarMaximum Reel Size 68"D x 48"W x 2,500 lbs.
- 12" Medium Duty Tensioning Brake Package:
  - 12" Tension Brake with 12" x 5/8" Solid Bronze Disc.  
Cast Steel Caliper and Tension Adjusting Handle
  - (1) pair - 36"H Reel Stands with Heavy Duty Bronze Bearings
  - (1) 2-7/8" Reel Bar with (1) Crossarm and  
(1) Locking Collar
- Maximum Reel Size 68"D x 48"W x 3,000 lbs.

### Hitch & Jack

- 3" Lunette Eye (In Lieu of 2-1/2" Eye)
- Visible Registration Holder
- Full Width Jack Handle Extension  
Add to One Side  
Add to Both Sides (Requires Store-Away Handle)

### Cargo Bed

- (4) - 9"Wide x 9" Deep Open Top Storage Bins  
Located Front and Rear of Fenders to  
Roll-Off Fender Guards
- Additional D-Rings
- Chains on Tailgate

### Wiring & Light Bar

- Light Bar
  - (2) Rubber Mounted Sealed Beam Lights (Stop Turn and Tail)
  - 36"L x 4" x Tubular Steel Body
  - Chain Adjusted Mounting Base
  - 25' of Cable with 6-Way Aluminum Die Cast Connector
- Warner 6-Way Connector in Lieu of Standard 6-Way Connector
- Solar Charged Breakaway Kit In Lieu of Standard Kit