



Power Unit

RT 7200

7200

The newest tractor to join the Ventrac line-up is the 7200. This power unit features Hydrostatic Front-Wheel-Drive, Variable-Speed Piston Wheel Motors, and Power Steering which gives the operator enhanced maneuverability and agility over traditional tractors.

Ventrac's patented S.D.L.A. control, located next to the operator, allows for easy control of Speed, Direction, Lift and Auxiliary function all with one hand. The 7200 also comes standard with the Ventrac Minute Mount System which enables the operator to quickly and easily switch between attachments and jobs. Since the attachment is placed out front of the unit, the operator has a natural view offering greater precision as well as maximum protection.

With so many Ventrac Minute Mount attachments to choose from you can perform a variety of tasks. From mowing to blowing, scooping to brooming, pushing to pulling, all from one rear steered unit. The Ventrac 7200 has the versatility to meet your needs.



Standard Features:

- 31 HP Turbo Diesel Liquid Cooled Engine
- Rear Wheel Steering Control
- Front Wheel Drive
- Electric High - Low Control
- S.D.L.A. controls Speed, Direction, Lift, and Auxiliary hydraulics from a single point
- Heavy Duty 2 Speed Hydrostatic Wheel Motors
- Weight Transfer System
- Ventrac Minute Mount System
- Foot Control
- Tilt Steering Column
- Folding Roll Bar
- Suspension Seat
- AND MORE!



Dealer:



H.E.R.S. Inc.
1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718

Specifications

Power Unit RT 7200

7200

Stock Code	RT7200
RT7200 Turbo Diesel	39.71205
Engine	
Vanguard 31hp Turbo Diesel (Engine Model DM950DT)	Liquid Cooled 953 cc
Electrical	
Battery	450 Cold Cranking amps
Voltage	12 Volts
Alternator	40 amp
Powertrain	
Hydraulic Pump & Motors	Sauer/Danfoss Series 15
Wheel Motor	Poclairn 2-Speed Piston
Hydraulic Oil Cooler	Standard
Hydraulic Oil Filter	25 micron
Tires	
Standard Drive Tires	Turf Master (24x12-12 in) (61x30-30 cm)
Optional Drive Tires	All Trail (24x12-12 in) (61x30-30 cm)
Rear Tires	Turf Master (18x9.5-8 in) (53x28-20 cm)

Dimensions	RT7200
Wheelbase	55 Inches (140 cm)
Length	81 inches (206 cm)
Width w/Fieldtrax tires	54 inches (137 cm)
Height (top of Roll Bar)	78 inches (198 cm)
Turning Radius	14 inches (36 cm)
Weight (apprx.)	1600 lbs (725 kgs)
Fuel Capacity	12 gal. (US) (45.4 L)
Travel Speed*	
High Range	15 mph (24 kph)
Shipping Weight (Crated)	1820 lbs (825 kg)
Shipping Dimensions	85 x 59 x 48 inches (216 x 150 x 122 cm)

Instrument Panel

Standard Indicators	Tachometer/Hourmeter, Engine Coolant Temperature, Low Oil Indicator, Voltmeter, Glow Plug Light (diesel), PTO Switch/Indicator Light, Fuel
---------------------	--------------------------------------------------------------------------------------------------------------------------------------------

Standard Features

Roll Bar	Fold-Down
PTO	Electric Clutch
Steering	Power
Easy Shift	Standard

* Travel Speeds may vary with tire size, pressure, and engine RPM.
- All specifications subject to change without notice or obligation.



Dealer:



H.E.R.S. Inc.
1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718