



H.E.R.S. Inc.
 1203 South Parker
 Olathe, Kansas 66061
 Phone: (913) 764-6718

Redmax Brushcutter Specifications

- A variety of brushcutter blades are available for specific applications in the field.
- The vibration-reduction system is collar-type and integrated within the die-cast aluminum fan housing
- Self-lubricating, bronze, olite bearings support solid-steel drive shafts, resulting in superior low-friction performance
- Gear box with standard zerk fittings makes lubrication and maintenance simple and also ensures a longer product life.
- Die-cast aluminum fan housing maximizes heat dissipation and prolongs the life of the clutch-drum bearings.
- Redmax equipment provides users with perfectly balanced and positioned handles and controls for a great ergonomic fit.

Model	Engine Size	Engine	Horse-power	Dry Weight (*1)	Fuel Capacity	Warranty (*2)		Available in California
	CC	Type	HP	Lbs.	Fl. Oz.	Cons.	Com.	
BCZ3001SW	29.5	Strato	1.4	11.9	24.3	2 Yrs.	2 Yrs.	BCZ3001SW-CA
BC3401DL	33.6	2-Stroke	1.6	12.5	25.0	2 Yrs.	2 Yrs.	n/a
BC4401DW	41.5	2-Stroke	2.0	15.0	31.8	2 Yrs.	2 Yrs.	BC4401DW

(*1) Without cutting head and strap.

(*2) Ignition coil includes lifetime warranty.