



**H.E.R.S. Inc.**  
 1203 South Parker  
 Olathe, Kansas 66061  
 Phone: (913) 764-6718

## Redmax Chain Saw Specifications/Features

- For maximum strength, die-cast aluminum engine bodies are available on most models.
- Durable aluminum bar mount is included for improved safety, performance and durability.
- Throttle-lever lock prevents unintentional engine acceleration for even greater safety.
- MaxClean air filtration system removes up to 90% of debris before it enters the air filter.
- Pre-cleaned using centrifugal force, the intake system allows only clean air into the intake track, reducing the need for air filter maintenance in the field.
- Designed with unique features that reduce or eliminate all kickback that occurs in the field.

Model	Engine Size		Engine Type	Horse-power	Dry Weight	Fuel Capacity	Chain Oil System Speed	Bar Length	Warranty		Available in California
	Cu. In.	CC		HP	Lbs.	Fl. Oz.		Inches	Cons.	Com.	
PSZ2401	1.4	23.6	Strato	1.1	10.9	21.3	Adjust., Auto.	12	2 Yrs.	1 Yr.	PSZ2401-CA
G3100T	1.8	30.1	2-Stroke	1.6	7.6	7.4	Automatic	12, 14	2 Yrs.	1 Yr.	n/a
GZ3500T <b>NEW</b>	2.15	35.2	Strato	1.94	7.3	8.4	Adjust., Auto.	12, 14	2 Yrs.	1 Yr.	GZ3500T
G3800AVS	2.3	37.2	2-Stroke	2.2	9.1	10.5	Automatic	16, 18	2 Yrs.	1 Yr.	n/a
GZ400	2.4	40.1	Strato	2.4	9.7	10.5	Automatic	16, 18	2 Yrs.	90 Days	GZ400
GZ4000	2.4	40.1	Strato	2.4	9.5	10.5	Automatic	16, 18	2 Yrs.	1 Yr.	GZ4000
GZ4500	2.7	44.0	Strato	2.5	9.6	10.5	Adjust., Auto.	16, 18	2 Yrs.	1 Yr.	GZ4500
G5000AVS	3.0	49.3	2-Stroke	3.6	11.2	18.6	Adjust., Auto.	18, 20	2 Yrs.	1 Yr.	G5000AVS
G5300 <b>NEW</b>	3.23	53.0	2-Stroke	3.3	11.0	16.9	Adjust., Auto.	16, 18, 20	2 Yrs.	1 Yr.	G5300
G621AVS	3.8	62.0	2-Stroke	4.1	12.5	22.6	Adjust., Auto.	20, 24	2 Yrs.	1 Yr.	G621AVS
GZ7000 <b>NEW</b>	4.14	67.9	Strato	4.9	14.7	23.0	Adjust., Auto.	20, 24, 28	2 Yrs.	1 Yr.	GZ7000