



## Specifications

### Silver Eagle 2750

#### Engine:

- Generac 27Hp vertical shaft V-twin four-cycle air cooled engine.
- 27 HP output at 3750 RPM.
- 760 cc displacement.
- Electric start.
- Gear driven oil pump.
- Engine mounted replaceable 25 micron Generac oil filter.
- Pulse fuel pump.
- Dual-stage Donaldson air cleaner with Turbo pre-cleaner.
- Low oil warning horn (98db).

#### Electrical:

- 12 Volt, 300 cold cranking amps, maintenance free battery.
- 20 amp alternator/stator with regulator-rectifier.
- Operator presence system.  
By shutting off the deck, setting the parking brake, and returning the steering levers to the neutral lock, the operator can leave the seat without the engine turning off.

#### Fuel Capacity:

- 6.0 US Gallons.

#### Gauges:

- Hour meter with integrated PTO, Brake, and Volt indicator light.

#### Drive system:

- (2) White Hydraulic 10 c.c. pumps.
- (2) White Hydraulics CE series hydraulic motors; 13.7 cu. in. displacement with 1-1/2" axle and integral brake.
- (2) 40-micron hydraulic filters.
- (2) Hand-operated forward/reverse steering/braking controls.
- 2.5 gallon hydraulic reservoir.
- External remote-mounted hydraulic oil cooler.
- Lubrication: Lucas 15w40 Magnum.

**Controls:**

- Foot operated mower deck height adjustment.
- (2) Hand operated steering control levers with dampner system
- Hand operated PTO switch
- Throttle control.
- Ignition switch.
- Choke.
- Positive lock drum-type parking brake.
- Operator controlled discharge chute "OCDC"

**Steering:**

- Independent control of drive wheels through steering control levers.

**Brakes:**

- Dynamic braking through steering levers.
- Parking brake gives positive lockup of drive wheels when applied.

**Main Frame:**

- All welded two-rail tube frame using 2" X 2" (7 gauge) steel tubing.
- Lifetime warranty on front caster assembly and bearings.
- Stainless steel fenders with cup holder.
- Seat with armrests.
- Flip up floor pan.
- Engine Guard.

**Mower Deck:**

- Welded baffles.
- Electric Clutch.
- Deck height adjusts straight up and down so pitch is always constant.
- Floating deck mounted to rigid frame (does not run on the ground).
- Deck rollers to prevent scalping.
- Keyless sealed spindles.
- 1-1/4" Effective diameter spindle shafts with self-tightening spindle assembly.

**Deck Materials:**

- Ten (10) gauge shell (.135" thickness).
- 3/16" (.187") reinforcing top plate (bolted, not welded)



**Deck Materials con't.:**

- Total thickness in critical area = .322".
- One piece cast iron deck spindle housing.
- Vented, split 3/16" steel deep groove pulleys.

**Tires/Wheels:**

- Rear: 24" X 12" X 12" Turf Master tubeless ATV type 4-ply rating (6-8 lbs air pressure).
- Front: 13" X 6.50" X 6" tubeless 4-ply rating.

**Ground Speed:**

- 0-10 mph forward and reverse.

**Cutting Height:**

- 1" - 5"

**Cut Width:**

- 50"

**Machine Width:**

- 54"

**Length:**

- 75.5"

**Weight**

- 1026 lbs.

**Warranty\***

- Three-Year Bumper to Bumper, two year parts and labor, 3rd year parts.
- Lifetime on front fork caster assemblies.
- Lifetime on front forks against breakage
- Lifetime on steering levers
- Three-Year deck spindle
- Dixie Chopper meets and exceeds all ANSI standards

\* See Authorized Dixie Chopper Dealer for details

- Specifications are subject to change.