



Tiller KL480

4000
series

The KL480 Tiller is designed for easy preparation of gardens and yards. This power-driven front-end attachment allows the operator to easily monitor the Tiller's performance. Designed with VENTRAC's Minute Mount System, the Tiller can be attached in a minute or less and comes with a stand for storing the Tiller when not in use.

A number 80 chain in an enclosed final drive is lubricated for heavy-duty performance. Skid shoe adjustments facilitate cutting depth. Twenty-four carbon tines are sequentially spaced to maximize the cutting force.



Standard Features:

- Intermediate Gear Reduction for Quiet Running
- Sealed Lubrication Final Drive
- Leveler Shield
- Skid Shoe Adjustments
- 24 High-Performance Carbon Tines
- Stand for holding attachment when not in use
- Ventrac Minute Mount System



Dealer:



H.E.R.S. Inc.
1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718

Specifications

Tiller KL480

4000
series

KL480

Stock Code	39.55220
Working Width	48 inches (122 cm)
Tines	24
Maximum tilling depth	6 inches (15.24 cm)
Final Drive	#80 Chain, enclosed and lubricated
Ground Clearance	Approx. 10 inches (25.4 cm) raised

Dimensions

Length	41 inches (104 cm)
Width	53 inches (135 cm)
Height	22 inches (56 cm)
Weight	356 lbs (162 kg)
Shipping Weight	425 lbs (193 kg)
Shipping Dimensions (L x W x H)	57x43x25 inches (145x109x64 cm)

All specifications subject to change without notice or obligation



Dealer:



H.E.R.S. Inc.
1203 South Parker
Olathe, Kansas 66061
Phone: 913.764.6718